

AMINO A125



MULTI CODEC IP-STB

The A125 is a multi-codec set-top box (STB) designed for IPTV and Video-on-Demand (VoD) applications

With an Ethernet input and highly flexible audio and video outputs, the A125 provides an elegant and powerful means of delivering sophisticated interactive digital television - including multicast, Video-on-Demand (VoD) and Internet access. The advanced low-cost chipset used in the A125 features a combined programmable codec DSP and host processor. This enables development of new services to increase revenue per subscriber while offering protection against changing standards.

Increase return on investment

Advanced codecs such as H.264 and WMV9 use lower bitrates enabling more customers to be served with the same infrastructure and increasing the reach of DSL networks.

Reduce the cost of AVC transition

Multiple codec capability enables the same STB to be used on legacy and advanced networks eliminating the need for a truck-roll when the infrastructure is upgraded.

Compact and elegant

Supplied in a compact and elegant enclosure, based on the award-winning A100 design, the A125 adds style to the most visible component of an IPTV deployment.

Extensive ecosystem support

The A125 is supported by an extensive ecosystem of middleware, browser, conditional access and DRM options required for the widely varying configurations of the IPTV market.

Comprehensive design tools and support

Amino software technology is based on open standards such as Linux and HTML. Application developers for the A125 benefit from the Amino JMACX system which enables full control of the STB functions from the browser. JMACX provides the service operator with a powerful set of HTML and JavaScript extensions which allow simple and highly effective user interface designs to be created or ported. For increased flexibility in creating custom applications ADKs and SDKs are also available.

To find out more about the A125 please contact an Amino representative today.

“Supplied in a compact and elegant enclosure, the A125 adds style to the most visible component of an IPTV deployment.”





AMINO A125

Software updates and maintenance

The A125 holds a complete software image in on-board flash memory and is also designed to support secure bootstrap from a multicast server. At any time, a deployed A125 can be upgraded with a new software image via the secure multicast server. The multicast approach ensures that very large numbers of deployed set-top boxes can be upgraded without placing an individual load on the server or the network. For security, software images can be signed with keys unique to each deployment.

About Amino Communications

Amino is the world leading independent IPTV specialist, delivering entertainment solutions for pure and hybrid IPTV, Over-The-Top (OTT) Internet video and in-home multimedia distribution. Amino delivers a range of award-winning set-top boxes and software to over 800 customers in 80 countries, including telecoms operators, service providers, broadcast, enterprise and hospitality companies. Amino also boasts the industry's widest range of pre-integrated IPTV ecosystems.

Amino's 'AssetHouse' modular asset management solution allows telecoms companies, content producers, broadcasters and web TV companies to profit from their on-demand services.

Detailed Specification A125 - Multi Codec IP-STB

Size and weight	114mm x 100mm x 35mm. 270g (excluding accessories and packaging)
Inputs	Ethernet 10/100 BaseT via RJ-45 shielded connector
Outputs	10-way Mini-DIN for Composite video, Component (YPrPb), RGB, S-Video and analogue audio. S/PDIF (RCA). USB2.0. RF Loop through and Modulator
Power	5.2V DC at 1.2A via external power supply 6W typical usage (external supply input voltage 100-240V AC 50-60Hz 0.8A max)
Codecs	MPEG-2 MP@ML MPEG-4 MP@L3 VC1 (WMV9)
Video resolutions	PAL and NTSC
Graphics resolutions	640x438 (NTSC) and 640x512 (PAL)
Audio	Analogue stereo audio out. Stereo and Dolby 5.1 surround via S-PDIF (coax). Dolby Digital pass through to external decoder
Security	Wide selection of DRM and Conditional Access support. Macrovision (Option)
Memory	32MB Flash, 128MB RAM
Front panel LEDs	Standby/IR command received (Red)
Smart card interface	ISO-7816

Operating environment	ETS 300-019-1-3 Class 3.1
EMC conformance	FCC Part 15 class B. 2004/108/EC EN55022
Safety approvals	CAN/ CSA-C22.2 No. 60065-03 EN60065
RoHS	2002-95-EC
WEEE	2002-96-EC
Operating temperature	0°C (32°F) to 40°C (104°F)
Storage humidity	5% to 95% RH (non-condensing)

Accessories

Remote control	Standard
Regional power supply with power cord	Standard
Anti-slip base	Standard
IR keyboard	Optional
SCART cable	Optional
Component (YPrPb) cable	Optional
S-VHS & Composite (CVBS) cable	Optional
RGB cable	Optional



Global Headquarters

Amino Communications Limited
Buckingham Business Park
Anderson Road, Swavesey
Cambridge CB24 4UQ
United Kingdom

Tel: +44-1954-234100
Fax: +44-1954-234101
Email: info@aminocom.com

Americas

Amino Communications LLC
3625 Brookside Parkway
Suite 150
Alpharetta GA 30022
USA

Tel: +1-678-636-6000
Fax: +1-678-636-6001
Email: info@aminocom.com

China

Amino Communications
Technology Service Co Ltd
Suite 2702, City Gateway
398 Caoxi Lu, Shanghai 200030
China

Tel: +86-21-3368-8423
Email: cninfo@aminocom.com

London

Amino Communications Limited
6th Floor
32 Duke Street, St James's
London SW1Y 6DF
United Kingdom

Tel: +44-20-7747-9300
Fax: +44-20-7747-9301
Email: info@aminocom.com

Sweden

Amino Communications AB
Finlandsgatan 40
SE-164 74 Kista
Sweden

Tel: +46-8-5625-1600
Email: info@aminocom.com

Amino, AmiNET, AssetHouse, Mood and the Amino Logo are trademarks of Amino Communications Limited. All other trademarks are the property of their respective owners. © Amino Communications Ltd 2009.

